

County Surveyor's Record, Douglas County, Oregon

16484

Dependet Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE
T 24 S R 6 W
S 27 | S 26
S 34 | S 35
1969

from which the remains of the original bearing trees

A root hole, bears N. 1 1/2° E., 40 lks. dist., with a down oak alongside, 32 ins. diam., with axe marks visible on decayed blaze.

An oak, 35 ins. diam., bears S. 68 1/2° E., 87 lks. dist., with healed blaze.

A root hole, bears S. 37 1/2° W., 313 lks. dist., with a down oak, alongside, size indeterminate, no marks visible.

A decayed oak stump, size indeterminate, bears N. 68° W., 47 lks. dist., with axe marks visible on decayed blaze.

and bearing tree mkd. by Powell

A fir, 16 ins. diam., bears N. 16° E., 58 lks. dist., with healed double blaze.

A white oak, 7 ins. diam., bears S. 63° E., 32 lks. dist., with healed double blaze.

A madrone, 18 ins. diam., bears S. 76° W., 36 lks. dist., with scribe marks 24S R6W S34 CS BT visible on open double blaze.

A madrone, 18 ins. diam., bears N. 46° W., 58 lks. dist., with illegible scribe marks visible on partially healed double blaze.

North, bet. secs. 26 and 27, marking and blazing the true line.

Ascend 40 ft. over SE. slope, through heavy timber and dense undergrowth.

3.50 Woven wire fence, extending N. 5° E. and S.

7.15 Spur, slopes E.; desc. 55 ft. over NE. slope.

17.10 Creek, 5 lks. wide, course S. 65° E.; asc. 35 ft. over SE. slope.

20.01 Point for the S 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 27 | S 26
1979

from which

A fir, 6 ins. diam., bears N. 44° E., 46 1/2 lks. dist., mkd. S 1/16 S26 BT.

A fir, 10 ins. diam., bears N. 43 1/2° W., 43 lks. dist., mkd. S 1/16 S 27 BT.