

County Surveyor's Record, Douglas County, Oregon

16485

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 115 ft. over SE. slope.
30.35	Spur, slopes E.; desc. 60 ft. over NE. slope.
35.95	Creek, 1 lk. wide, course S. 75° E.; asc. 25 ft. over SE. slope.
38.20	Spur, slopes N. 50° E.; desc. 35 ft. over NE. slope.
40.02	The 1/4 sec. cor. of secs. 26 and 27, perpetuated and recorded by Milton B. Germond, Deputy County Surveyor, in 1908, determined at record bearing and distance from the remains of the original bearing trees: <p style="margin-left: 40px;">A laurel, 36 ins. diam., bears S. 48° E., 39 lks. dist., with axe marks visible on decayed blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 44° W., 19 lks. dist.</p> <p>and the remains of a bearing tree mkd. by Germond</p> <p style="margin-left: 40px;">A root hole, bears S. 3° W., 143 lks. dist., with a down oak alongside, 20 ins. diam., with axe marks visible on decayed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 24 S R 6 W <i>FD. OK 10-92 R. DOLAN</i></p> <p style="margin-left: 100px;">1/4 <i>M 116-12</i></p> <p style="margin-left: 100px;">S 27 S 26</p> <p style="margin-left: 100px;">1979</p> </div> <p>from which new bearing trees</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears S. 65° E., 28 lks. dist., mkd. 1/4 S26 BT.</p> <p style="margin-left: 40px;">A fir, 18 ins. diam., bears S. 73° W., 66 lks. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 30%; margin: 20px auto;"/> <p>N. 0° 09' E., beginning new measurement.</p> <p>Descend 70 ft. over NE. slope.</p>
3.45	Woven wire fence, extending N. 25° W. and S. 25° E.
3.85	Creek, 5 lks. wide, course S. 60° E.; asc. 165 ft. over SE. slope.
12.70	Dirt road, 20 lks. wide, bears N. 30° W. and S. 30° E.
15.45	Spur, slopes E.; desc. 185 ft. over NE. slope.
25.05	Ravine, drains N. 80° E.; asc. 30 ft. over SE. slope.
27.95	Spur, slopes N. 80° E.; desc. 210 ft. over NE. slope.
36.50	Leave timber, enter open pasture land, edge bears N. 40° W. and S. 40° E.
37.10	Williams Creek Road, gravelled, 30 lks. wide, bears N. 50° W. and S. 55° E.
37.45	Woven wirefence, extending N. 50° W. and S. 50° E.