

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

16486

CHAINS

40.50

The cor. of secs. 22, 23, 26, and 27, reestablished by proportionate measurement by Floyd J. Cole, Deputy County Surveyor, in 1915, and perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1956, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 24 S R 6 W
S 22 | S 23
S 27 | S 26
1956

from which the remains of a bearing tree mkd. by Cole

A root hole, bears S. 82 1/2° E., 134 lks. dist.

and the remains of bearing trees mkd. by Byron

An ash, 15 ins. diam., bears N. 9 1/2° E., 145 lks. dist., with scribe marks 6W visible on partially healed double blaze.

A sawed oak stump, 18 ins. diam., bears N. 87 1/2° E., 67 lks. dist., no marks visible.

and new bearing trees

An ash, 7 ins. diam., bears S. 65° E., 463 lks. dist., mkd. X BT.

A fir, 14 ins. diam., bears S. 30° W., 352 lks. dist., mkd. T24S R6W S27 BT.

An ash, 20 ins. diam., bears N. 6° W., 241 lks. dist., mkd. T24S R6W S22 BT.

Corner is located in woven wire fence, extending E. and W.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, cedar, hemlock, oak, madrone, ash, maple, and alder; undergrowth, poison oak, vine maple, blackberry, thimbleberry, huckleberry, hawthorne, fern, Oregon grape, wild rose, arrowwood, hazel, and young timber.

From the cor. of secs. 26, 27, 34, and 35.

N. 89° 35' W., bet. secs. 27 and 34.

Ascend 200 ft. over broken SE. slope, through heavy timber and dense undergrowth.

16.06

From this point, the NW. cor. of Donation Land Claim No. 41, bears South, 0.205 chs. dist., perpetuated and recorded by William F. Briggs, Deputy County Surveyor, in 1891, from original evidence no longer in existence, further perpetuated and recorded by John N. Powell, Deputy County Surveyor, in 1969, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.