

County Surveyor's Record, Douglas County, Oregon

16487

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

NW COR
DLC 41
1969

from which the remains of a bearing tree mkd. by Briggs

An oak snag, 24 ins. diam., bears West, 15 lks. dist., with scribe marks BT visible on opened double blaze.

and a bearing tree mkd. by Powell

An oak, 14 ins. diam., bears N. 29° E., 10 lks. dist., with healed double blaze.

19.94 Woven wire fence, extending N. and S., 25 lks. north of fence corner, with fences extending N., E., and W.

20.09 Point for the E 1/16 sec. cor. of secs. 27 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S\ 27}{S\ 34}$
1979

from which

A fir, 14 ins. diam., bears N. 2 1/4° W., 61 lks. dist., mkd. E 1/16 S27 BT.

A fir, 18 ins. diam., bears S. 59° E., 14 1/2 lks. dist., mkd. E 1/16 S34 BT.

Ascend 400 ft. over SE. slope, changing to E. slope.

37.50 Summit of Gross Mountain, bears N. 10° E. and S. 10° W.; desc. 20 ft. over SW. slope, also dirt road, 15 lks. wide, bears N. and S.

40.18 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 6 W
1/4 $\frac{S\ 27}{S\ 34}$
1979

from which

A fir, 4 ins. diam., bears N. 73 1/4° E., 22 1/2 lks. dist., mkd. X BT.

A fir, 5 ins. diam., bears S. 8 1/2° E., 24 lks. dist., mkd. 1/4 S34 BT.

Corner is located 25 lks. south of woven wire fence, extending E. and W.

Descend 290 ft. over SW. slope.