

# County Surveyor's Record, Douglas County, Oregon

16489

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

21.80 Creek, 3 lks. wide, course S. 80° W.; asc. 340 ft. over SW. slope.

40.01 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 6 W  
1/4  
S 28 | S 27  
1979

from which

A fir, 4 ins. diam., bears S. 51 1/2° E., 70 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 55 1/2° W., 55 lks. dist., mkd. 1/4 S28 BT.

Ascend 325 ft. over SW. slope.

59.55 Leave timber, enter burned over area, edge bears E. and W.

66.25 Summit of Gross Mountain, bears N. 85° W. and S. 85° E.; desc. 455 ft. over NW. slope, also dirt road, 15 lks. wide, bears E. and W.

80.02 Point for the cor. of secs. 21, 22, 27, and 28, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 6 W  
S 21 | S 22  
S 28 | S 27  
1979

from which

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 50° E., 40 lks. dist., with brass cap mkd. T24S R6W S22 RM 40 LKS 1979 and an arrow pointing to the corner.

A fir, 6 ins. diam., bears S. 35 1/2° E., 41 lks. dist., mkd. T24S R6W S27 BT.

A maple, 12 ins. diam., bears S. 47 1/2° W., 168 lks. dist., mkd. T24S R6W S28 BT.

Set a 5 ft. steel fence post alongside iron post.

Corner is located in open field.

From this point, the cor. of secs. 15, 16, 21, and 22, bears N. 0° 12' E., 80.02 chns. dist., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.