

County Surveyor's Record, Douglas County, Oregon

16490

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

S 16 | S 15
S 21 | S 22
T 24 S R 6 W
1958

from which the remains of an original bearing tree

A sawed fir stump, 48 ins. diam., bears S. 17° W.,
132 lks. dist., with fragmentary scribe marks
visible on decayed blaze.

and bearing trees mkd. by Byron

A white oak, 16 ins. diam., bears N. 63 1/2° E., 250
lks. dist., with healed blaze.

A white oak, 15 ins. diam., bears S. 33 1/2° E., 68
lks. dist., with healed blaze.

A fir, 25 ins. diam., bears S. 65° W., 285-1/2 lks.
dist., with healed blaze.

Corner is located in open pasture, no tree available
to the NW.

From this same point, the cor. of secs. 19, 20, 29, and
30, bears N. 89° 56' W., 160.55 chs. dist., perpetuated
and recorded by F. C. Frear, Deputy County Surveyor, in
1932, from original evidence no longer in existence, and
further perpetuated and recorded by James W. Byron, Deputy
County Surveyor, in 1958, monumented with an iron post,
2 1/2 ins. diam., firmly set, projecting 6 ins. above ground,
with brass cap. mkd.

T 24 S R 6 W
S 19 | S 20
S 30 | S 29
1962

from which bearing trees mkd. by Frear

A white oak, 25 ins. diam., bears N. 14° E., 39
lks. dist., with healed double blaze.

A white oak, 16 ins. diam., bears S. 15° E., 32
lks. dist., with healed double blaze.

A white oak, 15 ins. diam., bears S. 38° W., 33
lks. dist., with healed double blaze.

A white oak, 16 ins. diam., bears N. 67° W., 30
lks. dist., no marks visible on decayed blaze.

and bearing trees mkd. by Byron

A white oak, 17 ins. diam., bears S. 77° E., 10
lks. dist., with healed double blaze.

A white oak, 14 ins. diam., bears N. 45° W., 66
lks. dist., with illegible scribe marks visible
on partially healed double blaze.

and bearing trees mkd. by Gawron

A white oak, 30 ins. diam., bears S. 24° E., 37
lks. dist., with healed blaze.