

County Surveyor's Record, Douglas County, Oregon

16495

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 32 S R 7 W

S 17 | S 16

S 20 | S 21

1967

from which the original bearing trees

A live oak, 9 ins. diam., bears N. 16 1/2° E., 31 lks. dist., with opened blaze, no marks visible. (Record N. 10° E.)

A ponderosa pine, 28 ins. diam., bears S. 41° E., 56 lks. dist., with healed blaze, and scribe marks R7W S21 BT visible on partially healed blaze. (Record S. 45° E.)

A live oak, 8 ins. diam., bears S. 6° W., 19 lks. dist., no marks visible.

A ponderosa pine, 22 ins. diam., bears N. 57° W., 33 lks. dist., with opened blaze, no marks visible.

and bearing trees mkd. by Powell

A fir, 20 ins. diam., bears N. 48° E., 39 lks. dist., with healed blaze.

A fir, 15 ins. diam., bears S. 1° W., 40 1/2 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 7° W., 54 1/2 lks. dist., with healed blaze.

N. 1° 10' E. bet. secs. 16 and 17, marking and blazing the true line.

Ascend 490 ft. over SW. slope, through heavy timber and moderate undergrowth.

21.70 Spur, slopes S. 40° E.; asc. 85 ft. along E. slope, changing to SE. slope.

36.00 Ridge, dividing Dad's Creek and Sled Creek, bears N. 40° E. and S. 40° E.; desc. 105 ft. over NW. slope.

39.32 Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 7 W

1/4

S 17 | S 16

1978

from which

A fir, 8 ins. diam., bears N. 88 1/2° E., 53 lks. dist., mkd. 1/4 S16 BT.

A fir, 6 ins. diam., bears S. 38° W., 82 lks. dist., mkd. 1/4 S17 BT.

Descend 590 ft. over broken NW. slope.