

County Surveyor's Record, Douglas County, Oregon

16498

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Corner is located at top of precipitous rock bluff. 150 ft. high.

Ascend 165 ft. over NE. slope.

39.29 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 7 W

1/4 $\frac{S\ 20}{S\ 29}$

1978

from which

A fir, 12 ins. diam., bears N. 36 1/2° E., 43 lks. dist., mkd. 1/4 S20 BT.

A ponderosa pine, 19 ins. diam., bears S. 9° E., 61 1/2 lks. dist., mkd. 1/4 S29 BT.

Ascend 160 ft. over NE. slope.

39.50 Dirt road, 25 lks. wide, bears N. 75° E., and N. 5° W., in curve.

52.80 Top of ascent, slopes N; desc. 85 ft. over NW. slope.

56.60 Bottom of descent, slopes NE.; asc. 90 ft. over NE. slope.

63.00 Top of ascent, slopes NE.; desc. 215 ft. over NW. slope.

65.60 Dirt road, 25 lks. wide, bears N. 40° E. and S. 40° W.

67.30 Dirt road, 25 lks. wide, bears N. 30° E. and S. 30° W.

78.58 The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 32 S R 7 W

S 19 | S 20

S 30 | S 29

1967

from which the remains of the original bearing trees

A burned fir stump, size indeterminate, bears N. 58 1/2° E., 70 lks. dist., no marks visible (Record, N. 55° E.)

A hollow madrone, 23, ins. diam., bears S. 11 1/2° E., 58 lks. dist., no marks visible. (Record S. 15° E.)

A hollow madrone, 16 ins. diam., bears S. 48° W., 38 lks. dist., no marks visible. (Record, S 55° W.)

A cedar, 25 ins. diam., bears N. 1° W., 29 lks. dist., with scribe marks BT visible on bark blaze. (Record, N. 5° W.)