

County Surveyor's Record, Douglas County, Oregon

16500

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears N. 38 1/2° W., 23 lks.
dist., mkd. T32S R7W S18 BT.

N. 89° 34' W., bet. secs. 18 and 19.

Ascend 25 ft. over SE. slope, through heavy timber and
dense undergrowth, across partially logged area.

1.80 Top of ascent, slopes S.; desc. 60 ft. over SW. slope.

5.80 Susan Creek Road, gravelled, 25 lks. wide, bears
S. 65° E. and S. 55° W., in curve, and bottom of descent,
slopes S.; asc. 125 ft. over SE. slope.

12.30 Spur, slopes SW.; desc. 240 ft. over NW. slope.

12.80 Susan Creek Road, gravelled, 25 lks. wide, bears
N. 30° E. and S. 45° W., in curve.

24.00 Bottom of descent, slopes W.; asc. 15 ft. along S. slope.

31.00 Spur, slopes SW.; desc. 195 ft. over Steep SW. slope.

36.50 Ravine, drains SW.; asc. 30 ft. along S. slope.

39.27 The 1/4 sec. cor. of secs. 18 and 19, determined at record
bearing and distance from the only remaining original
bearing tree:

A black oak, 27 ins. diam., bears S. 89° W., 116
lks. dist., with scribe marks 1/4 B visible on
opened blaze. (Record, live oak)

and a bearing tree of which I have no record

A fir, 21 ins. diam., bears N. 54 1/2° E., 60 lks.
dist., with scribe marks BT visible on opened
blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 32 S R 7 W
1/4 $\frac{S 18}{S 19}$
1978

from which new bearing trees

A fir, 19 ins. diam., bears N. 71 1/4° W., 32 1/2 lks.
dist., mkd. 1/4 S18 BT.

A fir, 20 ins. diam., bears S. 65° W., 59 lks.
dist., mkd. 1/4 S19 BT.

N. 89° 48' W., beginning new measurement.

Ascend 10 ft. over SE. slope.

1.30 Spur, slopes SW.; desc. 245 ft. over steep SW. slope.

10.33 Point for the E W 1/64 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.