

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

16502

CHAINS

T 32 S
R 8 W R 7 W
S 13 | S 18
S 24 | S 19
1958

from which the remaining original bearing trees

A madrone, 13 ins. diam., bears N. 30° E., 75 lks. dist., with opened blaze, no marks visible.

A fir, 27 ins. diam., bears S. 55° W., 23 lks. dist., with opened and burned blaze, no marks visible.

A live oak, 16 ins. diam., bears N. 58 1/4° W., 76 lks. dist., with scribe marks R8W S13 visible on opened blaze.

and bearing trees mkd. by Theilsen

A fir, 23 ins. diam., bears N. 17° E., 85 lks.

dist., with healed blaze.
A fir, 18 ins. diam., bears S. 71 1/2° E., 54 lks.

dist., with healed blaze.
A fir, 22 ins. diam., bears S. 71° W., 74 lks.

dist., with healed blaze.

A fir, 21 ins. diam., bears N. 75 1/2° W., 47 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, madrone, oak, yew, maple, and alder; undergrowth, poison oak, manzanita, willow, ceanothus, wild rose, blackberry, huckleberry, Oregon grape, salal, and fern.

From the cor. of secs. 17, 18, 19, and 20.

N. 1° 03' E., bet. secs. 17 and 18.

Ascend 160 ft. over SE. slope, through heavy timber and dense undergrowth, along W. edge of partially logged area.

6.30 Spur, slopes SW.; asc. 70 ft. over SW. slope.

11.30 Spur, slopes N. 80° W.; desc. 540 ft. over NW. slope.

23.15 Susan Creek Road, gravelled, 25 lks. wide, bears N. 85° E. and S. 70° W., in curve.

31.45 Sled Creek, 20 lks. wide, course S. 80° W.; asc. 295 ft. over S. slope.

38.59 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance, there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.