

County Surveyor's Record, Douglas County, Oregon

16506

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears N. 28 1/2° E., 42 lks.
dist. mkd. S 1/16 S8 BT.

A fir, 6 ins. diam., bears S. 84 1/2° W., 112 lks.
dist., mkd. S 1/16 S7 BT.

Ascend 65 ft. over SW. slope.

24.20 Spur ridge, bears E. and W.; desc. 450 ft. over N. slope.

26.00 Susan Creek Road, dirt, 15 lks. wide, bears NE. and SW.

39.71 Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 7 W
1/4
S 7 | S 8
1978

from which

A fir, 13 ins. diam., bears S. 34° E., 60 1/2 lks.
dist., mkd. 1/4 S8 BT.

A fir, 12 ins. diam., bears S. 39° W., 79 1/2 lks.
dist., mkd. 1/4 S7 BT.

Descend 300 ft. over N. slope.

49.00 Susan Creek, 10 lks. wide, course S. 80° W.; asc. 520 ft. over S. slope.

57.30 Susan Creek Road, dirt, 15 lks. wide, bears E. and W.

79.42 The cor. of secs. 5, 6, 7, and 8, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 32 S R 7 W
S 6 | S 5
S 7 | S 8
1968

from which the original bearing trees remarked by Powell

A ponderosa pine, 25 ins. diam., bears N. 65° E., 32 lks. dist., with healed original blaze and scribe marks 7W S BT visible on partially healed blaze. (Record, N. 68° E.)

A ponderosa pine, 25 ins. diam., bears S. 57 1/2° E., 26 lks. dist., with scribe marks 7W visible on opened original blaze and scribe marks 7W visible on partially healed blaze. (Record, S. 52° E.)

A ponderosa pine, 20 ins. diam., bears S. 15° W., 10 lks. dist., with burned out original blaze and scribe marks T32S R7W S7 CS BT visible on open blaze.