

# County Surveyor's Record, Douglas County, Oregon

16508

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS  
82.60

The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp., perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

|   |            |   |
|---|------------|---|
|   | T 32 S     |   |
| R | S 1   S 6  | R |
| 8 | S 12   S 7 | 7 |
| W | 1967       | W |

from which the remains of the original bearing trees

A sawed and decayed pine stump, size indeterminate, bears N. 83° E., 11 lks. dist., no marks visible.

A root hole, bears S. 48 1/2° E., 141 lks. dist.,

A root hole, bears S. 8° W., 66 lks. dist.,

and bearing trees mkd. by Powell

A fir, 16 ins. diam., bears N. 65 1/2° E., 57 lks. dist., with pitched over partially healed blaze.

A madrone, 11 ins. diam., bears S. 41° E., 6 1/2 lks. dist., with scribe marks T32S R7W S7 CS BT. visible on partially healed blaze.

A fir, 17 ins. diam., bears S. 40 1/4° W., 29 1/2 lks. dist., with pitched over partially healed blaze.

A fir, 13 ins. diam., bears N. 53 1/2° W., 20 1/2 lks. dist., with pitched over partially healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, oak, chinquapin, cedar, maple, and yew; undergrowth, poison oak, manzanita, hazel, ceanothus, mountain lilac, salal, Oregon grape, and fern.

Remonumentation of Certain Original Corner Points,  
T. 32 S., R 7 W., Willamette Meridian, Oregon

The following field notes describe the remonumentation of certain original corner points, township 32 south, range 7 west, Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group Number 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories when Needed."

The remonumentation of original corner points was made at the request of the District Manager, Medford, for administrative purposes of the Bureau of Land Management.

East Boundary, T. 32 S., R. 7 W.,  
Willamette Meridian, Oregon

(Remonumenting a corner established by Wells Lake and George W. Hyde, U. S. Deputy Surveyor, in 1855, and rehabilitated by Willam H. Byars, U. S. Deputy Surveyor, in 1881)