

# County Surveyor's Record, Douglas County, Oregon

16509

Remonumentation of Certain Original Corner Points,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

The cor. of secs. 25, 30, 31, and 36, on the E. bdy of the Tp., perpetuated and recorded by T. H. Mehl, III, Registered Land Surveyor No. 749, in 1967, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:

A burned fir snag, 48 ins. diam., bears N. 51° E., 19 1/2 lks. dist., with scribe mark S visible on opened and burned blaze. (Record, 17 lks.)

A root hole, bears S. 52° E., 16 lks. dist., with a down burned and decayed fir alongside, 40 ins. diam., with decayed blaze, no marks visible. (Record, 14 lks.)

A sawed and burned fir stump, 36 ins. diam., bears N. 24° W., 19 lks. dist., with illegible scribe marks visible on opened blaze. (Record, 17 lks.)

and bearing trees mkd. by Mehl

A white fir, 12 ins. diam., bears S. 78° E., 117 lks. dist., with healed blaze.

A ponderosa pine, 10 ins. diam., bears S. 28 3/4° E., 29 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
R 7 W   R 6 W
S 25   S 30
S 36   S 31
1978

from which new bearing trees

A fir, 10 ins. diam., bears N. 12° E., 65 lks. dist., mkd. T32S R6W S30 BT.

A ponderosa pine, 7 ins. diam., bears S. 40° W., 148 1/2 lks. dist., mkd. T32S R7W S36 BT.

A fir, 30 ins. diam., bears N. 82 1/4° W., 158 lks. dist., mkd. T32S R7W S25 BT.

Reset iron pipe alongside iron post.

Subdivisions, T. 32 S., R. 7 W.,  
Willamette Meridian, Oregon

(Remonumenting corners established by William H. Byars,  
U. S. Deputy Surveyor, in 1881)

The 1/4 sec. cor. of secs. 25 and 26, determined at record bearing from the original bearing trees:

A root hole, bears N. 88° E., 32 lks. dist., with a down and decayed fir alongside, 40 ins. diam., no marks visible.