

County Surveyor's Record, Douglas County, Oregon

16510

Remonumentation of Certain Original Corner Points,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 52 ins. diam., bears N. 30° W.,
54 lks. dist., with scribe marks 1/4 S BT visible
on bark blaze. (Record, 52 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 32 S R 7 W
1/4
S 26 | S 25
1978

from which new bearing tress

A live oak, 12 ins. diam., bears N. 17° E., 37 lks.
dist., mkd. 1/4 S25 BT.

A sugar pine, 10 ins. diam., bears S. 24° W., 8
lks. dist., mkd. 1/4 S26 BT.

The 1/4 sec. cor. of secs. 21 and 22, perpetuated and re-
corded by Norman D. Price, Registered Land Surveyor No.
33, in 1954, and further perpetuated by John M. Powell,
Deputy County Surveyor, in 1967, monumented with an iron
pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above
ground, from which the remains of an original bearing
tree:

A sawed fir stump, 40 ins. diam., bears N. 55° E.,
33 lks. dist., with scribe marks 1/4 S visible
on bark blaze. (Record, 31 lks.)

and a bearing tree mkd. by Price

A fir, 16 ins. diam., bears N. 77 1/2° W., 84 lks.
dist., with healed blaze.

and a bearing tree mkd. by Powell

A fir, 14 ins. diam., bears S. 89° E., 64 1/2 lks.
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, directly over iron pipe, with brass cap
mkd.

T 32 S R 7 W
1/4
S 21 | S 22
1978

The 1/4 sec. cor. of secs. 15 and 16, determined at record
bearing from the remains of the original bearing trees:

A sugar pine, snag, 60 ins. diam., bears S. 50° E.,
34 lks. dist., with illegible scribe marks
visible on detached portion of bark. (Record,
31 lks.)

A madrone with burned out center, 20 ins. diam.,
bears N. 48° W., 70 lks. dist., no marks visible.