

# County Surveyor's Record, Douglas County, Oregon

16511

Remonumentation of Certain Original Corner Points,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 7 W  
1/4  
S 16 | S 15  
1978

from which new bearing trees

A fir, 9 ins. diam., bears N. 71 1/2° E., 63 lks. dist., mkd. 1/4 S15 BT.

A fir, 25 ins. diam., bears N. 64 1/2° W., 61 lks. dist., mkd. 1/4 S16 BT.

The 1/4 sec. cor. of secs. 21 and 28, perpetuated and recorded by Norman D. Price, Registered Land Surveyor No. 33, in 1954, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of the original bearing trees:

A pine stump, 28 ins. diam., bears N. 42° W., 17 lks. dist., with healed double blaze. (Record N. 45° W.)

A pine stump, 24 ins. diam., bears S. 35° W., 22 lks. dist., with healed double blaze. (Record, S. 38° W.)

and the remains of bearing trees mkd. by Price

A dead topped tan oak, 6 ins. diam., bears N. 60° E., 18 1/2 lks. dist., with scribe marks 1/4 S21 RS33 BT visible on partially healed blaze.

A tan oak snag, 5 ins. diam., bears S. 5° W., 26 lks. dist., with scribe marks 1/4 S28 RS33 BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 32 S R 7 W  
1/4 S 21  
S 28  
1978

from which a new bearing tree

A fir, 7 ins. diam., bears S. 13° E., 43 lks. dist., mkd. 1/4 S28 BT.

The 1/4 sec. cor of secs. 16 and 21, determined at record bearing and distance from the remains of an original bearing tree:

A sawed and shattered fir stump, 36 ins. diam., bears N. 65° W., 34 lks. dist., with illegible scribe marks visible on detached bark blaze.