

County Surveyor's Record, Douglas County, Oregon

16515

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

(Restoring the survey by Edward F. Sharp,
U. S. Deputy Surveyor, in 1893, and
the remonumentation by James E. Jelley,
Cadastral Surveyor, in 1962)

Beginning at the 1/4 sec. cor. of secs. 1 and 2, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 33 S R 4 W
1/4
S 2 | S 1
1971

from which the remains of the original bearing trees

A root hole, bears S. 27° E., 30 lks. dist., with a down fir alongside, 40 ins. diam., with scribe mark 4 visible on opened and decayed blaze.

A fir, 30 ins. diam., bears N. 24° W., 42 lks. dist., with healed blaze.

and bearing trees mkd. by Evans, in 1971

A fir, 9 ins. diam., bears S. 41° E., 55 lks. dist., with scribe marks 1/4 S1 BT visible on partially healed blaze.

A fir, 20 ins. diam., bears S. 4 1/2° W., 55 1/2 lks. dist., with scribe marks 1/4 S2 BT visible on partially healed blaze.

N. 0° 02' W., bet. secs. 1 and 2, marking and blazing the true line.

Descend 125 ft. over NE. slope, through medium timber and moderate undergrowth, along E. edge of logged area.

3.95 Dry creek bed, 1 lk. wide, course S. 70° E., asc. 325 ft. over S. slope, changing to SE. slope.

13.70 Spur, slopes S. 65° E.; desc. 15 ft. over NE. slope.

14.56 An original line tree, a fir, 44 ins. diam., mkd. with 2 notches on N. and S. sides.

N. 0° 06' E., beginning new measurement.

Descend 110 ft. over NE. slope.

3.15 Wet ravine, drains E.; asc. 35 ft. over SE. slope.

5.30 Top of ascent, slopes E.; desc. 175 ft. over NE. slope.

15.45 Wet ravine, drains S. 80° E.; asc. 260 ft. over SE. slope.

23.51 Intersect the S. bdy. of T. 32 S., R. 4 W. (Seventh Standard Parallel South).

True point for the closing cor. of secs. 1 and 2.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.