

# County Surveyor's Record, Douglas County, Oregon

16517

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 33 S., R. 4 W., Willamette Meridian, Oregon

**CHAINS**

From the cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

T 33 S R 4 W  
S 3 | S 2  
S 10 | S 11  
1962

from which the remaining original bearing trees

A fir, 58 ins. diam., bears S. 80° E., 26 lks. dist., with healed blaze.

A fir, 40 ins. diam., bears S. 65° W., 85 lks. dist., with healed blaze.

and the remains of a bearing tree mkd. by Jelley

A root hole, bears N. 51 1/2° W., 74 lks. dist., with a down and burned fir alongside, 7 ins. diam., with illegible scribe marks visible on partially healed blaze.

and new bearing trees

A hemlock, 10 ins. diam., bears N. 10 1/2° E., 116 lks. dist., mkd. T33S R4W S2 BT.

A chinquapin, 10 ins. diam., bears N. 29° W., 82 lks. dist., mkd. T33S R4W S3 BT.

N. 0° 01' E., bet. secs. 2 and 3.

Descend 85 ft. over NE. slope, through medium timber and dense undergrowth.

13.15 Grave Creek, 15 lks. wide, course S. 20° E.; asc. 10 ft. along creek bottom.

21.00 Leave Grave Creek, course S. from N. 20° W.; asc. 225 ft. over SW. slope.

23.30 Road, asphalt surfaced, 30 lks. wide, bears N. 40° W. and S. 20° E.

38.35 Spur, slopes S. 60° W.; desc. 10 ft. along W. slope.

40.58 The 1/4 sec. cor. of secs. 2 and 3, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears S. 35° E., 16 lks. dist., with a down fir alongside, 38 ins. diam., with scribe marks BT visible on partially healed blaze.

A root hole bears S. 72° W., 15 lks. dist., with a down fir alongside, 26 ins. diam., with scribe marks 1/4 visible on partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 33 S R 4 W  
1/4  
S 3 | S 2  
1975