

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 4 W., Willamette Meridian, Oregon

16518

CHAINS

from which new bearing trees

A fir, 6 ins. diam., bears S. 70 3/4° E., 70 1/2 lks. dist., mkd. 1/4 S2 BT.

A fir, 37 ins. diam., bears N. 61 1/2° W., 87 lks. dist., mkd. 1/4 S3 BT.

N. 0° 36' E., beginning new measurement.

Descend 175 ft. over NW. slope.

8.00 Grave Creek, 10 lks. wide, course S. 30° W.; asc. 285 ft. over SE. slope.

10.40 Road, asphalt surfaced, 30 lks. wide, bears N. 20° E. and S. 40° W.

34.84 The original closing cor. of secs. 2 and 3, monumented with the original basalt stone, 18 x 12 x 6 ins., firmly set 10 ins. in the ground, mkd. with 2 grooves on E., 4 grooves on W., and CC on S. faces, from which the remains of the original bearing trees:

A fir snag, 32 ins. diam., bears S. 59° E., 82 lks. dist., with scribe mark S visible on partially opened and burned blaze.

A shattered fir stump, 40 ins. diam., bears S 22° W., 68 lks. dist., no marks visible.

Add marks AM to corner stone and bury in original position.

Continue over SE. slope.

34.87 Intersect the S. bdy. of T. 32 S., R. 4 W., (Seventh Standard Parallel South).

True point for the closing cor. of secs. 2 and 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W
S 35
S 3 | S 2
C C
T 33 S
1975

from which

A cedar, 12 ins. diam., bears S. 11 1/2° E., 69 lks. dist., mkd. T33S R4W S2 CC BT.

A fir, 6 ins. diam., bears S. 87° W., 52 lks. dist., mkd. T33S R4W S3 CC BT.

From this point, the former standard cor. of secs. 34 and 35, changed to an angle point by Chapman and Nicklin, in 1897, bears S. 89° 31' E., 23.365 chs. dist., described in the field notes of the dependent resurvey of the S. bdy. of T. 32 S., R 4 W., executed concurrently under this same group.