

County Surveyor's Record, Douglas County, Oregon

16520

Dependent Resurvey, Portion of Subdivisional Lines,
T. 33 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The true point for the closing corner of secs. 3 and 4, located in gravelled road, 30 lks. wide, bears N. 20° W. and S. 20° E.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 32 ins. in the ground, the top 4 ins. below surface of the road, with brass cap mkd.

T 32 S
S 34
S 4 | S 3
C C
T 33 S R 4 W
1975

from which

A fir, 10 ins. diam., bears S. 13° E., 64 lks. dist., mkd. T33S R4W S3 CC BT.

A fir, 7 ins. diam., bears S. 88 1/2° W., 20 lks. dist., mkd. T33S R4W S4 CC BT.

From this point, the original closing cor. of secs. 3 and 4, bears N. 0° 42' E., 0.045 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:

A fir root crown, size indeterminate bears N. 55 1/2° E., 111 lks. dist., no marks visible.

A root hole, bears S. 63 1/4° E., 137 lks. dist.,

A burned fir stump, 38 ins. diam., bears S. 89° W., 80 lks. dist., with burned blaze.

From this same point, the former standard cor. of secs. 33 and 34, changed to an angle point by Chapman and Nicklin, in 1897, bears S. 89° 37' E., 24.63 chs. dist., described in the field notes of the dependent resurvey of the S. bdy. of T. 32 S., R. 4 W., executed concurrently under this same group.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, madrone, chinquapin, alder, yew, and hemlock; undergrowth, ceanothus, manzanita, vine maple, rhododendron, Oregon grape, fern, and young timber.

The point for the 1/4 sec. cor. of sec. 3 only, T. 33 S., R. 4 W., is at midpoint on the N. bdy. of sec. 3.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 4 ft. base to top; with brass cap mkd.

1/4 S 3
T 33 S R 4 W
1975

from which

A cedar, 8 ins. diam., bears S. 70 1/2° E., 26 1/2 lks. dist., mkd. 1/4 S3 BT.

A fir, 18 ins. diam., bears S. 44° W., 281 1/2 lks. dist., mkd. 1/4 S3 BT.