

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary  
(Seventh Standard Parallel South),  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

16528

**CHAINS**

20.76 True point for the closing cor. of secs. 1 and 2, T. 33 S., R. 4 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 33 S., R. 4 W., executed concurrently under this same group.

Ascend 105 ft. over SE. slope.

27.15 True point for the closing cor. of secs. 35 and 36, hereinafter described.

Corner is located on spur, slopes N. 80° E.

Thence S. 89° 37' W., continue measurement on the S. bdy. of sec. 35.

Ascend 200 ft. over E. slope of spur.

39.29 Point for the former standard 1/4 sec. cor. of sec. 35, changed to an angle point by Chapman and Nicklin, determined by the method of irregular boundaries; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 1  
T 32 S R 4 W  
S 35  
1975

from which

A fir, 36 ins. diam., bears N. 27 1/2° E., 108 1/2 lks. dist., mkd. AP1 S35 BT.

A fir, 6 ins. diam., bears N. 6 1/2° W., 114 1/2 lks. dist., mkd. AP1 S35 BT.

Corner is located on spur, slopes E.

S. 89° 30' W., beginning new measurement.

Ascend 460 ft. over NE. slope.

4.00 Leave logged area, edge bears NE. and SW.; enter heavy timber.

18.70 Main ridge dividing West Fork of Evans Creek and Graves Creek drainages, bears N. 20° E. and S. 10° W.; desc. 205 ft. over NW. slope, changing to W. slope.

27.22 Point for the 1/4 sec. cor. of sec. 35 only, hereinafter described.

Descend 305 ft. over W. slope.

38.11 The former standard cor. of secs. 34 and 35, changed to an angle point by Chapman and Nicklin, determined at record distance from the original bearing trees:

A fir, 23 ins. diam., bears N. 40 1/2° E., 40 lks. dist., with scribe marks SC R4W visible on partially opened blaze. (Record, N. 32° 50' E.)