

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary,
 (Seventh Standard Parallel South),
 T. 32 S., R. 4 W., Willamette Meridian, Oregon

16530

CHAINS

AP 1
 T 32 S R 4 W
S 34
 1975

from which new bearing trees

A fir, 9 ins. diam., bears N. 12 1/2° E., 157 lks.
 dist., mkd. AP1 S34 BT.

A cedar, 7 ins. diam., bears N. 30 3/4° W., 9 lks.
 dist., mkd. AP1 S34 BT.

Deposit corner stone alongside iron post.

Corner is located at top of cut bank of road, edge bears
 NW. and SW., and on a spur, slopes E.

N. 89° 41' W., beginning new measurement.

Ascend 55 ft. over E. slope of spur.

9.425 Point for the E 1/16 sec. cor. of sec. 34 only, hereinafter described.

Ascend 30 ft. over E. slope of spur.

14.00 Leave spur, slopes S. 80° E.; asc. 140 ft. over broken SE. slope.

24.315 Point for the 1/4 sec. cor. of sec. 3 only, T. 33 S., R. 4 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 33 S., R 4 W., executed concurrently under this same group.

Ascend 30 ft. along S. slope.

26.85 Trail, bears N. 30° E. and S. 30° W.

27.00 Rocky spur ridge, bears N. and S.; desc. 5 ft. over SW. slope.

29.695 Point for the 1/4 sec. cor. of sec. 34 only, hereinafter described.

Descend 140 ft. over SW. slope.

30.95 Dirt road, 10 lks. wide, bears N. and S.

37.35 Head of ravine, drains SW.; asc. 10 ft. over SE. slope.

39.96 The former standard cor. of secs. 33 and 34, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County Surveyors Office, in 1970, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W S33 S34 SSC T33S 1970, from which the remains of an original bearing tree:

A fir snag, 18 ins. diam., bears N. 45° E., 19 lks.
 dist., with scribe marks BT visible on opened
 double blaze.

and bearing trees mkd. by the County Surveyors Office