

County Surveyor's Record, Douglas County, Oregon

16531

Dependent Resurvey of the South Boundary
(Seventh Standard Parallel South),
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 27 ins. diam., bears N. 49° E., 29 1/2 lks. dist., with scribe marks T32S R4W SSC34 CS BT visible on pitched over double blaze.

A fir, 30 ins. diam., bears N. 7° W., 31 lks. dist., with scribe marks T32S R4W SSC33 CS BT visible on pitched over double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 2
T 32 S R 4 W
S 34
1975

Reset county iron post alongside iron post.

Land, mountainous.
Soil, rocky clay with rock outcroppings.
Timber, fir, cedar, pine, madrone, chinquapin, alder, yew, maple, and hemlock; undergrowth, manzanita, ceanothus, vine maple, rhododendron, poison oak, salal, Oregon grape, fern, and young timber.

N. 89° 37' W., on the S. bdy. of sec. 34.

Ascend 25 ft. over SE. slope, through scattering timber and dense undergrowth, across partially logged area.

4.00 Spur, slopes S. 20° W.; desc. 265 ft. over SW. slope.

24.50 Gravelled road, 30 lks. wide, bears N. 20° W. and S. 20° E.

24.63 True point for the closing cor. of secs. 3 and 4. T. 33 S., R. 4 W., described in the field notes of the dependent resurvey of a portion of the subdivisional lines, T. 33 S., R. 4 W., executed concurrently under this same group.

Corner is located in gravelled road, 30 lks. wide, bears N. 20° W. and S. 20° E.

Descend 150 ft. over SW. slope.

29.85 Creek, 1 lk. wide, course S. 40° W.; desc. slightly along S. slope.

30.275 True point for the closing cor. of secs. 33 and 34, hereinafter described.

Thence N. 89° 37' W., continue measurement on the S. bdy of sec. 33.

Descend 25 ft. over SW. slope.

31.30 Last Chance Creek, 2 lks. wide, course S. 20° E.; asc. 225 ft. over NE. slope.

34.50 Gravelled road, 30 lks. wide, bears N. 10° W. and S. 10° E.