

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary,  
 (Seventh Standard Parallel South),  
 T. 32 S., R. 4 W., Willamette Meridian, Oregon

16532

CHAINS

38.91

The former standard 1/4 sec. cor. of sec. 33, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County Surveyors Office, in 1970, monumented with a mound of stone, 3 ft. base, 1 1/2 ft. high, from which the remains of an original bearing tree:

A cedar, 22 ins. diam., bears S. 50° W., 25 lks. dist., with scribe marks 4 SC visible on partially opened double blaze. (Record, fir)

and bearing trees mkd. by the County Surveyors Office

A fir, 34 ins. diam., bears N. 52° E., 23 1/2 lks. dist., with scribe marks S 1/4 C S33 CS BT visible on pitched over double blaze.

A fir, 12 ins. diam., bears N. 38° W., 19 lks. dist., with scribe marks S 1/4 C S33 CS BT visible on pitched over double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

AP 1  
 T 32 S R 4 W  
 S 33  
 1975

S. 89° 13' W., beginning new measurement.

Ascend 50 ft. over E. slope.

2.60

Main ridge dividing Graves Creek and Starvout Creek drainages, bears N. 30° E. and S. 20° W.; desc. 140 ft. over NW. slope.

14.50

Head of ravine, drains N. 20° W.; asc. 100 ft. over NE. slope.

22.80

Rocky spur, slopes N. 10° W.; desc. 160 ft. over SW. slope.

27.00

Power transmission line, bears N. 50° W. and S. 50° E.

29.25

Gravelled road, 25 lks. wide, bears N. 10° E. and S. 10° W.

30.525

Point for the 1/4 sec. cor. of sec. 33 only, at midpoint longitudinally on the S. bdy. of sec. 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W  
 1/4 S 33  
 1975

from which

A fir, 6 ins. diam., bears N. 68° E., 30 1/2 lks. dist., mkd. 1/4 S33 BT.

A cedar, 6 ins. diam., bears N. 4° W., 10 lks. dist., mkd. 1/4 S33 BT.