

County Surveyor's Record, Douglas County, Oregon

16535

Dependent Resurvey of the South Boundary
(Seventh Standard Parallel South),
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	Reset county iron post alongside iron post.
	S. 89° 20' W., beginning new measurement.
	Descend 175 ft. over SW. slope, through scattering timber and dense undergrowth.
4.45	Starvout Creek, 8 lks. wide, course N. 20° W.; asc. 15 ft. over NE. slope.
5.85	Top of ascent, slopes N. 10° E.; desc. 15 ft. over NW. slope.
7.25	Creek, 2 lks. wide, course N. 20° E.; asc. 135 ft. over SE. slope.
11.24	Point for the E 1/16 sec. cor. of sec. 32 only. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<u>E 1/16 S 32</u> 1975
	from which
	A cedar, 10 ins. diam., bears N. 60° E., 72 lks. dist., mkd. E 1/16 S32 BT.
	A fir, 12 ins. diam., bears N. 81° W., 10 lks. dist., mkd. E 1/16 S32 BT.
	Ascend 355 ft. over SE. slope, changing to E. slope.
23.00	Dirt road, 15 lks. wide, bears N. 20° E. and S. 10° E., in curve.
25.445	Point for the 1/4 sec. cor. of sec. 5 only, T. 33 S., R. 4 W., at midpoint longitudinally on the N. bdy. of sec. 5. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<u>1/4 S 5</u> T 33 S R 4 W 1975
	from which
	A cedar, 13 ins. diam., bears S. 21° E., 37 1/2 lks. dist., mkd. 1/4 S5 BT.
	A fir, 16 ins. diam., bears S. 31 1/2° W., 45 1/2 lks. dist., mkd. 1/4 S5 BT.
	Ascend 135 ft. over E. slope.
30.82	Point for the 1/4 sec. cor. of sec. 32 only, at midpoint longitudinally on the S. bdy. of sec. 32. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T 32 S R 4 W <u>1/4 S 32</u> 1975