

County Surveyor's Record, Douglas County, Oregon

16536

Dependent Resurvey of the South Boundary,
(Seventh Standard Parallel South),
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 18 ins. diam., bears N. 42° E., 14 lks.
dist., mkd. 1/4 S32 BT.

A fir, 12 ins. diam., bears N. 55° W., 44 lks.
dist., mkd. 1/4 S32 BT.

Ascend 25 ft. over E. slope.

33.00 Spur, slopes N. 40° E.; desc. 80 ft. over NW. slope.

35.20 Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W.

37.75 Bottom of descent, slopes N; asc. 5 ft. over NE. slope.

38.22 The former standard cor. of secs. 31 and 32, changed to an angle point by Chapman and Nicklin, monumented with a basalt stone, 12 x 10 x 10 ins. loosely set 3 ins. in the ground, mkd. SC on N., 5 grooves on E. and 1 groove on W. faces, from which the remains of the original bearing trees:

A fir snag, 23 ins. diam., bears N. 50° E., 36 lks.
dist., with scribe marks T34S visible on partially
opened double blaze. (Record, N 48° E.,)

A fir snag, 30 ins. diam., bears N. 50° W., 29 lks.
dist., with scribe marks SC T34S R4W S32 visible
on burned and open double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

AP 2
T 32 S R 4 W
S 32
1975

from which new bearing trees

A fir, 10 ins. diam., bears N. 36° E., 22 1/2 lks.
dist., mkd. AP2 S32 BT.

A cedar, 6 ins. diam., bears N. 59° W., 34 lks.
dist., mkd. AP2 S 32 BT.

Deposit corner stone alongside iron post.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, cedar, pine, madrone, chinquapin, and yew;
undergrowth, manzanita, vine maple, rhododendron, ceano-
thus, salal, Oregon grape, fern, and young timber.

N. 89° 01' W., on the S. bdy. of sec. 32.

Ascend 35 ft. over NE. slope, through medium timber and
dense undergrowth.

3.85 Top of ascent, slopes N.; desc. 60 ft. over broken NW.
slope.

13.20 Wet ravine, drains N. 20° E.; asc. 90 ft. over broken
NE. slope.