

# County Surveyor's Record, Douglas County, Oregon

16527

Dependent Resurvey of the South Boundary,  
(Seventh Standard Parallel South),  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
20.00	Creek, 1 lk. wide, course NE.; asc. 115 ft. over SE. slope.
23.98	<p>Point for the closing cor. of secs. 5 and 6, T. 33 S., R. 4 W., at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S S 32 S 6   S 5 C C T 33 S R 4 W 1975</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 2 1/4° E., 116 lks. dist., mkd. T33S R4W S5 CC BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 36° W., 134 1/2 lks. dist., mkd. T33S R4W S6 CC BT.</p> <p>Ascend 285 ft. over SE. slope, changing to E. slope.</p>
31.76	<p>The original closing cor. of secs. 31 and 32, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A fir snag, 35 ins. diam., bears N. 68 1/2° E., 91 lks. dist. with illegible scribe marks visible on burned blaze. (Record, N. 62 1/2° E., 97 lks.)</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 23 1/2° W., 25 lks. dist., with scribe mark B visible on partially opened blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 32 S R 4 W C C S 31   S 32 S 6 T 33 S 1975</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 32 ins. diam., bears N. 34 1/2° E., 112 lks. dist., mkd. T32S R4W S32 CC BT.</p> <p>Thence N. 89° 01' W., continue measurement on the S. bdy. of sec. 31.</p> <p>Ascend 205 ft. over E. slope, changing to NE. slope.</p>
38.81	<p>The former standard 1/4 sec. cor. of sec. 31, changed to an angle point by Chapman and Nicklin, perpetuated and recorded by the County Surveyors Office, in 1970, monumented with an iron post, 1 in. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd. COUNTY SURVEYORS OFFICE T32S R4W S1/4C S31 T33S 1970, from which the remains of the original bearing trees:</p>