

County Surveyor's Record, Douglas County, Oregon

16528

Dependent Resurvey of the South Boundary,
(Seventh Standard Parallel South),
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir stump, 18 ins. diam., bears N. 10° W., 23 1/2 lks. dist., with scribe marks 1/4 SC BT visible on open weathered double blaze. (Record, N. 30° E., 19 lks.)

A fir stump, 10 ins. diam., bears S. 27° W., 18 lks. dist., with scribe marks 1/4 SC visible on partially healed double blaze.

and bearing trees mkd. by the County Surveyors Office

A fir, 8 ins. diam., bears N. 39° E., 19 lks. dist., with scribe marks 1/4 SC 31 CS BT visible on partially healed double blaze.

A fir, 9 ins. diam., bears N. 26° W., 42 1/2 lks. dist., with scribe marks 1/4 SC 31 CS BT visible on partially healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 1
T 32 S R 4 W
S 31
1975

Reset county iron post alongside iron post.

N. 89° 01' W., beginning new measurement.

Ascend 70 ft. over NE. slope, through medium timber and dense undergrowth along N. edge of logged area.

- 2.70 Spur, slopes, N. 70° E.; desc. 20 ft. over NW. slope.
- 8.30 Bottom of descent, slopes N.; asc. 160 ft. over NE. slope.
- 17.50 Spur, slopes N. 30° W.; desc. 100 ft. over NW. slope.
- 25.36 Point for the 1/4 sec. cor. of sec. 6 only, T. 33 S., R. 4 W., at proportionate distance longitudinally on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

1/4 S 6
T 33 S R 4 W
1975

from which

A fir, 6 ins. diam., bears S. 37 1/4° E., 83 lks. dist., mkd. 1/4 S6 BT.

A fir, 31 ins. diam., bears S. 58 1/2° W., 49 1/2 lks. dist., mkd. 1/4 S6 BT.

Descend 190 ft. over NW. slope.

- 30.40 Head of ravine, drains N. 10° W.; asc. 40 ft. over NE. slope