

# County Surveyor's Record, Douglas County, Oregon

16541

Dependent Resurvey of the South Boundary,  
(Seventh Standard Parallel South),  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 32 S  
R S 1 | S 31 R  
5 T 33 S 4  
W 1964 W

from which an original bearing tree

A fir, 23 ins. diam., bears N. 47° E., 32 lks.  
dist., with scribe marks W S31 BT visible  
on partially opened blaze.

and a bearing tree recorded by Gawron, Jelley, and Aanrud

A fir, 10 ins. diam., bears S. 44° E., 17 lks.  
dist., with scribe marks T33S R5 S CC BT visible  
on partially healed double blaze. (Record,  
N. 28° W., 20 lks.)

and bearing trees mkd. by Gawron, Jelley, and Aanrud

A fir, 10 ins. diam., bears N. 72° E., 62 lks.  
dist., with illegible scribe marks visible on  
partially healed blaze.

A fir, 10 ins. diam., bears N. 39° W., 22 lks.  
dist., with illegible scribe marks visible on  
partially healed blaze.

Land, mountainous.

Soil, rocky clay with rock outcroppings.

Timber, fir, cedar, madrone, and chinquapin; undergrowth,  
ceanothus, salal, Oregon grape, arrowwood, hazel, fern,  
and young timber.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

(Restoring the survey by Winfield S. Chapman and  
Carl S. Nicklin, U. S. Deputy Surveyors, in 1897, and  
the remonumentation by Hans W. Thielsen,  
Cadastral Surveyor, in 1959)

From the 1/4 sec. cor. of secs. 35 and 36, monumented with  
an iron post, 2 1/2 ins. diam., firmly set, projecting 12  
ins. above ground, and in a mound of stone, 2 ft. base,  
to top, with brass cap mkd.

1/4  
S 35 | S 36  
T 32 S R 4 W  
1959

from which the remains of the original bearing trees

A sawed cedar stump, 23 ins. diam., bears N. 75° E.,  
99 lks. dist., no marks visible.

A pine, 40 ins. diam., bears S. 75° W., 17 lks.  
dist., with illegible scribe marks visible  
on partially healed blaze.

and a bearing tree recorded by Thielsen