

County Surveyor's Record, Douglas County, Oregon

16542

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A pine, 13 ins. diam., bears N. 46° E., 85 lks. dist., with scribe marks 1/4 S36 RS33 BT visible on partially healed blaze.

S. 0° 39' W., bet. secs. 35 and 36, marking and blazing the true line.

Descend 110 ft. over SE. slope, through medium timber and undergrowth, along W. edge of partially logged area.

6.20 Spur, slopes S. 30° E.; desc. 500 ft. over broken SW. slope.

22.00 Dry creek bed, 2 lks wide, course S. 10° E.; desc. 50 ft. over broken NE. slope.

31.70 Spur, slopes SE.; desc. 300 ft. over S. slope, changing to broken SE. slope.

39.78 From this point, a tree of which I have no record, bears East, 15 lks. dist.; a cedar, 8 ins. diam., with BT and other illegible scribe marks visible on partially healed double blaze.

48.95 Creek, 1 lk. wide, course E.; asc. 115 ft. over N. slope, changing to NE. slope.

58.575 The original closing cor. of secs. 35 and 36, determined at record bearing and distance from the original bearing trees:

A cedar, 50 ins. diam., bears N. 60° E., 45 lks. dist., with scribe marks W 36 visible on partially healed blaze.

A fir, 43 ins. diam., bears N. 12° W., 28 lks. dist., with healed blaze.

Continue along E. slope.

58.90 Intersect the S. bdy. of T. 32 S., R. 4 W. (Seventh Standard Parallel South).

True point for the closing cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W
C C
S 35 S 36
S 2
T 33 S
1975

from which

A cedar, 5 ins. diam., bears N. 73° E.; 47 lks. dist., mkd. T32S R4W S36 CC BT.

A fir, 5 ins. diam., bears N. 51 1/2° W., 86 1/2 lks. dist., mkd. T32S R4W S35 CC BT.

From this point, the former standard 1/4 sec. cor. of sec. 35, changed to an angle point by Chapman and Nicklin, bears S. 89° 37' W., 12.14 chs. dist., hereinbefore described.