

County Surveyor's Record, Douglas County, Oregon

16543

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, pine, madrone, chinquapin, and hemlock; undergrowth, manzanita, ceanothus, rhododendron, poison oak, vine maple, Oregon grape, fern, and young timber.

From the 1/4 sec. cor. of secs. 34 and 35, perpetuated and recorded by the County Surveyors Office, in 1970, monumented with an iron post, 1 in diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 32 S
DOUG | JACK
1/4 S 34 | S 35
CO | CO
R 4 W
1970

from which the remains of the original bearing trees

A fir root crown, bears N. 20° E., 47 lks dist., with illegible scribe marks on detached blaze.

A fir, 23 ins. diam., bears N. 21° W., 30 lks. dist., with healed blaze.

and a bearing tree mkd. by the County Surveyors Office

A fir, 16 ins. diam., bears S. 87° E., 50 lks. dist., with scribe marks 1/4 S35 CS BT visible on partially healed double blaze.

S. 0° 13' E., bet. secs. 34 and 35.

Descend 360 ft. over SW. slope, through heavy timber and dense undergrowth.

20.165 Point for the S 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 34 | S 35
1975

from which

A cedar, 42 ins. diam., bears S. 57 1/2° E., 49 lks. dist., mkd. S. 1/16 S35 BT.

A fir, 34 ins. diam., bears N. 45° W., 73 lks. dist., mkd. S 1/16 S34 BT.

Descend 490 ft. over S. slope.

31.45 Oiled surfaced road, 30 lks. wide, bears N. 80° W. and E.

40.33 Point for the 80 1/16 sec. cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

*Fd. B.C. 7/90
M 110-28*