

County Surveyor's Record, Douglas County, Oregon

18544

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

1/16
S 34 | S 35
80
1975

from which

A fir, 6 ins. diam., bears N. 81 1/2° E., 95 lks.
dist., mkd. 80 1/16 S35 BT.

A chinquapin, 8 ins. diam., bears N. 32 1/2° W., 46
lks. dist., mkd. 80 1/16 S34 BT.

Descend 140 ft. over S. slope.

46.70 Creek, 2 lks. wide, course E.; asc. 220 ft. over NE.
slope.

58.30 Spur, slopes S. 80° E.; desc. 5 ft. over E. slope.

59.34 Intersect the S. bdy. of T. 32 S., R. 4 W., (Seventh
Standard Parallel South).

True point for the closing cor. of secs. 34 and 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, and in a mound of stone, 3 ft. base, to
top, with brass cap mkd.

T 32 S R 4 W
C C
S 34 | S 35
S 3
T 33 S
1975

from which

A fir, 4 ins. diam., bears N. 36° E., 25 1/2 lks.
dist., mkd. X BT.

A fir, 10 ins. diam., bears N. 78° W., 78 lks.
dist., mkd. T32S R4W S34 BT.

From this point, the original closing cor. of secs. 34
and 35, bears S. 0° 13' E., 0.025 chs. dist., perpetuated
by person(s) unknown, monumented with a iron pipe, 3/4 in.
diam., firmly set, projecting 12 ins. above ground, from
which the original bearing trees:

A fir, 37 ins. diam., bears N. 45° E., 96 lks.
dist., with healed blaze.

A fir, 35 ins. diam., bears N. 44° W., 50 lks.
dist., with healed blaze.

From this same point, the former standard 1/4 sec. cor. of
sec. 34, changed to an angle point by Chapman and Nicklin,
bears N. 89° 31' W., 10.845 chs. dist., hereinbefore
described.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, pine, madrone, chinquapin, yew, alder,
maple, and hemlock; undergrowth, ceanothus, rhododendron,
poison oak, vine maple, Oregon grape, fern, and young
timber.