

# County Surveyor's Record, Douglas County, Oregon

18545

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

The point for the 1/4 sec. cor. of sec. 35 only, T. 32 S., R. 4 W., is at midpoint on the S. bdy. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 4 W  
1/4 S 35  
1975

from which

A fir, 12 ins. diam., bears N. 89° E., 7 1/2 lks. dist., mkd. 1/4 S35 BT.

A sugar pine, 22 ins. diam., bears N. 39° W., 80 lks. dist., mkd. 1/4 S35 BT.

From this point, the former standard cor. of secs. 34 and 35, changed to an angle point by Chapman and Nicklin, bears S. 89° 30' W., 10.89 chs. dist., herinbefore described.

From the 1/4 sec. cor. of secs. 33 and 34, monumented with the original basalt stone, 14 x 8 x 8 ins., firmly set 9 ins. in the ground, mkd. 1/4 on W. face, from which the remaining original bearing tree:

A live oak, 8 ins. diam., bears S. 5 1/2° W., 67 lks. dist., with illegible scribe marks visible on partially healed blaze. (Record, S. 7 1/2° W., 70 lks.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 32 S R 4 W  
1/4  
S 33 | S 34  
1975

from which new bearing trees

A fir, 10 ins. diam., bears S. 76 1/2° E., 50 1/2 lks. dist., mkd. 1/4 S34 BT.

A fir, 6 ins. diam., bears S. 83° W., 54 lks. dist., mkd. 1/4 S33 BT.

Deposit corner stone alongside iron post.

S. 0° 50' E., bet. secs. 33 and 34.

Descend 180 ft. over SW. slope, through medium timber and dense undergrowth.

10.70 Ravine, drains SW.; asc. 200 ft. over NW. slope.

19.70 Spur, slopes S. 80° W.; desc. 40 ft. along W. slope.

28.70 Main ridge dividing Grace Creek and Starvout Creek drainages, bears NE. and SW.; desc. 240 ft. over SE. slope.

38.65 Creek, 1 lk. wide, course SW.; asc. 65 ft. over NW. slope.