

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion
of the Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

16554

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, yew, pine, oak, madrone, alder, hemlock,
cedar, chinquapin, and maple; undergrowth, fern, poison
oak, vine maple, hazel, arrowwood, rhododendron, manzan-
ita, blackberry, Oregon grape, and young timber.

N. 2° 11' E., bet. secs. 2 and 3.

Descend 180 ft. over NE. slope, through moderate timber
and undergrowth.

- 6.50 Iron Mountain Creek, 5 lks. wide, course N. 50° W.; asc.
320 ft. over SW. slope.
- 21.50 Spur, slopes N. 80° W.; desc. 240 ft. over N. slope.
- 29.50 Creek, 3 lks. wide, course S. 75° W.; asc. 400 ft. over
S. slope.
- 40.74 The 1/4 sec. cor. of secs. 2 and 3, perpetuated and recorded
by James W. Byron, Deputy County Surveyor, in 1954,
further perpetuated and recorded by John M. Powell, Deputy
County Surveyor, in 1966, monumented with an iron post,
1 1/4 ins. diam., firmly set, projecting 12 ins. above
ground, in a mound of stone, 3 ft. base, to top, with
brass cap mkd.

COUNTY SURVEYORS OFFICE
T 31 S R 7 W
1/4 S 3 | S 2
1966

from which the remains of an original bearing tree

A pine snag, 32 ins. diam., bears S. 23° E., 35
lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A pine, 23 ins. diam., bears N. 77° E., 148 lks.
dist., with healed blaze.

A pine, 18 ins. diam., bears N. 16 1/2° W., 67 lks.
dist., with healed blaze.

Land, mountainous.
Soil, rocky clay.
Timber, fir, pine, yew, hemlock, maple, oak, madrone,
alder, and chinquapin; undergrowth, vine maple, hazel,
arrowwood, salal, Oregon grape, poison oak, rhododendron,
manzanita, fern, and young timber.

From the 1/4 sec. cor. of secs. 9 and 10, perpetuated and
recorded by John M. Powell, Deputy County Surveyor, in
1971, monumented with the original corner tree, a fir, 52
ins. diam., with healed blaze on W. side, this tree was
remarked by Powell, with scribe marks 1/4 S9/S10 visible
on bark, alongside of which is an iron post, 1 1/4 ins.
diam., firmly set, projecting 10 ins. above ground, with
brass cap mkd. COUNTY SURVEYORS OFFICE T31S R7 W 1/4 S9 S10
1971, from which the original bearing trees:

A oak, 20 ins. diam., bears S. 78° E., 52 lks.
dist., with decayed blaze, no marks visible.