

County Surveyor's Record, Douglas County, Oregon

Corrective Dependent Resurvey of a Portion
of the Subdivisional Lines,
T. 31 S., R. 7 W., Willamette Meridian, Oregon

16556

CHAINS

and bearing trees mkd. by Powell

A fir, 20 ins. diam., bears S. 69° E., 49 lks.
dist., with healed blaze.

A fir, 13 ins. diam., bears S. 43° W., 41 lks.
dist., with healed blaze.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, alder, chinquapin, pine, yew,
maple, and madrone; undergrowth, vine maple, hazel, salal,
arrowwood, huckleberry, Oregon grape, fern and rhodo-
dendron.

From the cor. of secs. 2, 3, 10, and 11.

N. 84° 39' W., bet. secs. 3 and 10.

Ascend 150 ft. over NE. slope, through moderate timber
and undergrowth.

- 3.10 Spur, slopes N.; desc. 60 ft. over NW. slope.
- 5.50 Creek, 2 lks. wide, course N. 25° E.; asc. 30 ft. over
NE. slope.
- 10.55 Ravine, drains N. 30° E.; asc. 180 ft. over NE. slope.
- 17.30 Spur, slopes N. 10° E.; desc. 130 ft. over NW. slope.
- 21.75 Ravine, drains N. 25° E.; asc. 130 ft. over NE. slope.
- 28.10 Spur, slopes N.; desc. 160 ft. over NW. slope.
- 34.70 Ravine, drains N. 10° E.; desc. 190 ft. over NW. slope.
- 41.38 The 1/4 sec. cor. of secs. 3 and 10, perpetuated and record-
ed by Gary Langlitz, Deputy County Surveyor, in 1974,
monumented with an iron post, 1 1/4 ins. diam., firmly set,
projecting 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4 $\frac{S\ 3}{S\ 10}$
T 31 S R 7 W
1974

from which the original bearing trees

A fir, 16 ins. diam., bears N. 60° E., 8 lks.
dist., with healed blaze.

A fir, 26 ins. diam., bears S. 45° W., 17 lks.
dist., with healed blaze.

and a bearing tree mkd. by Langlitz

A fir, 15 ins. diam., bears S. 43° E.; 28 lks.
dist., with healed blaze.

S. 88° 57' W., beginning new measurement.

Descend 230 ft. over NW. slope.