

County Surveyor's Record, Douglas County, Oregon

16580

T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

The geographic position of the corner of sections 3, 4, 33, and 34, as scaled from the Canyonville, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 59.9' N. Longitude 123° 24.3' W.

The mean magnetic declination is 19° 15' E.

Corrective Dependent Resurvey of a Portion
of the North Boundary,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by Nathaniel Ford,
U. S. Deputy Surveyor, in 1854,
the resurvey by Fred Mensch,
U. S. Deputy Surveyor, in 1905,
and correcting the resurvey by Hans W. Thielsen
and C. Albert White, Cadastral Surveyors, in 1958-59)

Beginning at the cor. of secs. 3, 4, 33, and 34, on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29	S R 6 W
S 33	S 34
S 4	S 3
T 30 S	
1958	

from which the remains of bearing trees mkd. by person(s) unknown and recorded by James W. Byron, Deputy County Surveyor, in 1956

A fir snag, 40 ins. diam., bears S. 9° E., 21 lks. dist., with scribe marks R BT visible on opened blaze.

A root hole, bears N. 4 1/2° W., 54 lks. dist., with a down fir alongside, 50 ins. diam., no marks visible on opened decayed blaze.

and the remains of bearing trees mkd. by Byron, in 1956

A decayed fir snag, size indeterminate, bears N. 62° E., 130 1/2 lks. dist., with illegible scribe marks visible on open blaze.

A fir, 25 ins. diam., bears S. 57° E., 59 lks. dist., with healed double blaze.

A fir, 26 ins. diam., bears N 20 1/2° W., 93 1/2 lks. dist., with healed double blaze.

and bearing trees mkd. by Roseberry

A fir, 15 ins. diam., bears N. 20 1/4° E., 118 1/2 lks. dist., with scribe marks T29S R6W S34 visible on partially healed blaze.

A fir, 17 ins. diam., bears S. 31° W., 52 1/2 lks. dist., with healed blaze. (Record, S. 3° W.)