

County Surveyor's Record, Douglas County, Oregon

16562

Corrective Dependent Resurvey of a Portion
of the North Boundary
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir, 16 ins. diam., bears S. 55 1/2° W., 56 1/2 lks. dist., with healed blaze.

Ascend 70 ft. over NE. slope.

48.20 Spur, slopes N. 20° E.; desc. 175 ft. over NW. slope.

56.90 Ravine, drains N.; asc. 140 ft. over NE. slope.

64.60 Spur, slopes N.; desc. 150 ft. over broken NW. slope.

77.08 True point for the closing cor. of secs. 32 and 33, T. 29 S., R. 6 W., from which the remaining bearing tree mkd. by Thielsen and White:

A cedar, 18 ins. diam., bears N. 24 1/2° W., 394 lks. dist., with healed blaze. (Record, N. 22 1/2° W., 378 lks.)

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 6 W
C C
S 32 | S 33
S 4
T 30 S R 6 W
1980

from which new bearing trees

A fir, 8 ins. diam., bears N. 73 1/2° E., 84 lks. dist., mkd. T29S R6W S33 CC BT.

A fir, 6 ins. diam., bears N. 49 1/2° W., 57 lks. dist., mkd. T29S R6W S32 CC BT.

The NE. bearing tree and the iron post set by Thielsen and White, in 1958-59, have been destroyed by logging activity.

From this point, the original closing cor. of secs. 32 and 33, bears N. 0° 06' W., 0.38 chs. dist., perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1956, and further perpetuated and recorded by A. Victor Cangle, Deputy County Surveyor, in 1976, monumented with an axle, 1 1/2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of an original bearing tree:

A fir snag, 24 ins. diam., bears N. 43° E., 31 lks. dist., with scribe marks 29W S33 BT visible on opened blaze.

and the remains of bearing trees mkd. by Markham

A fir, 50 ins. diam., bears N. 85° E., 145 lks. dist., with illegible scribe marks visible on bark.

A sawed cedar stump, 24 ins. diam., bears S. 30° W., 154 lks. dist., with scribe mark X visible on opened blaze.

and bearing trees mkd. by Cangle