

County Surveyor's Record, Douglas County, Oregon

16563

Corrective Dependent Resurvey of a Portion
of the North Boundary
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

A fir, 16 ins. diam., bears N. 50° E., 97 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 11 ins. diam., bears S. 8 1/4° W., 81 lks. dist., with illegible scribe marks visible on partially healed double blaze.

A fir, 12 ins. diam., bears N. 2 1/2° W., 93 lks. dist., with illegible scribe marks visible on partially healed double blaze.

Descend 5 ft. over NW. slope.

77.25 Creek, 1 lk. wide, course N. 20° E.; asc. 130 ft. over NE. slope.

83.80 Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.

87.00 Dirt road, 15 lks. wide, bears N. and S.

88.34 The cor. of secs. 4 and 5 only, T. 30 S., R. 6 W., moun-
mented with an iron post, 2 1/2 ins. diam., firmly set,
projecting 4 ins. above ground, with brass cap mkd.

T 29 S
S 32
S 5 | S 4
T 30 S R 6 W
1958

from which the remains of bearing trees mkd. by Mensch

A sawed fir stump, 44 ins. diam., bears S. 66° E.,
43 lks. dist., with burned blaze.

A fir snag, 36 ins. diam., bears S. 7° W., 25 lks.
dist., with burned blaze.

and the remains of bearing trees mkd. by Thielsen and
White

A sawed cedar stump, 20 ins. diam., bears S. 16 1/4° E.,
108 lks. dist., with illegible scribe marks
visible on partially healed blaze.

A sawed fir stump, 45 ins. diam., bears S. 39 1/2° W.,
94 lks. dist., with illegible scribe marks
visible on partially healed blaze.

and a bearing tree mkd. by Gary Langlitz, Deputy County
Surveyor, in 1974.

A fir, 13 ins. diam., bears N. 48° W., 52 1/2 lks.
dist., with healed blaze.

and new bearing trees

A fir, 5 ins. diam., bears S. 18° E., 52 lks.
dist., mkd. T30S R6W S4 BT.

A fir, 6 ins. diam., bears S. 47° W., 28 lks.
dist., mkd. T30S R6W S5 BT.

Land, mountainous.
Soil, rocky clay.