

County Surveyor's Record, Douglas County, Oregon

16565

Corrective Dependent Resurvey of a Portion
of the North Boundary
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which the remains of bearing trees mkd. by Thielsen and White</p> <p style="padding-left: 40px;">A cedar snag, 18 ins. diam., bears S. 51 1/2° E., 50 lks. dist., with scribe marks 1/4 S5 BT visible on open blaze.</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 31° W., 37 lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. 7 3/4° E., 154 lks. dist., mkd. 1/4 S5 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, cedar, pine, hemlock, oak, maple, madrone, and chinquapin; undergrowth, poison oak, wild rose, fern, arrowwood, hazel, blackberry, Oregon grape, and young timber.</p>
	<p>Dependent Resurvey of a Portion of the North Boundary, T. 30 S., R. 6 W., Willamette Meridian, Oregon</p>
	<p>(Restoring the survey by Nathaniel Ford, U. S. Deputy Surveyor, in 1854, the resurvey by Fred Mensch, U. S. Deputy Surveyor, in 1905, and the resurvey by Hans W. Thielsen and C. Albert White, Cadastral Surveyors, in 1958-59)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the 1/4 sec. cor. of sec. 5 only.</p> <p>N. 87° 59' W., on the N. bdy. of sec. 5, marking and blazing the true line.</p> <p>Ascend 10 ft. over SE. slope, through moderate timber and heavy undergrowth.</p>
1.30	Spur, slopes S.; desc. 185 ft. over SW. slope.
5.90	Dirt road, 20 lks. wide, bears N. 50° W. and S. 30° E.
19.59	Point for the W 1/16 sec. cor. of sec. 5 only.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>W 1/16 S 5 1980</p>
	from which
	A fir, 8 ins. diam., bears S. 12 3/4° E., 65 1/2 lks. dist., mkd. W 1/16 S 5 BT.
	A fir, 10 ins. diam., bears S. 20 1/2° W., 70 1/2 lks. dist., mkd. W 1/16 S5 BT.
	Descend 40 ft. over SW. slope.
27.29	From this point, the original closing corner of secs. 31 and 32, T. 29 S., R. 6 W., bears North, 35 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.