

County Surveyor's Record, Douglas County, Oregon

16566

Dependent Resurvey of a Portion of the North Boundary,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

C C
T 29 S R 6 W
S 31 | S 32
S 5
T 30 S
1958

from which the remains of the original bearing trees

A fir, 18 ins. diam., bears N. 61 1/2° E., 45 lks. dist., with healed blaze.

*Fd. OK
1/23/90
H. Johnson
c.s. 63/104*

and bearing trees mkd. by John H. Markham, Jr., Registered Engineer No. 2880, in 1956

A yew, 23 ins. diam., bears N. 51 1/2° E., 67 1/2 lks. dist., with scribe marks S32 T29S R6W BT visible on opened blaze.

A cedar, 18 ins. diam., bears S. 5 1/2° W., 48 lks. dist., with healed blaze.

and bearing trees mkd. by Thielsen and White

A fir, 25 ins. diam., bears N. 79° E., 61 lks. dist., with healed blaze.

A fir, 50 ins. diam., bears N. 53 1/2° W., 78 lks. dist., with scribe marks T29S R6W S31 BT visible on bark.

Descend 40 ft. over SW. slope.

39.18

The cor. of secs. 5 and 6 only, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S
S 31
S 6 | S 5
T 30 S R 6 W
1958

from which the remains of bearing trees mkd. by Mensch

A root hole, bears S. 43° W., 29 lks. dist., with a down fir alongside, 34 ins. diam., with healed blaze.

and the remains of bearing trees mkd. by Thielsen and White

A fir snag, 18 ins. diam., bears S 43 3/4° E., 102 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

A fir, 28 ins. diam., bears S. 23° W., 95 lks. dist., with healed blaze.

and a bearing tree of which I have no record

A fir, 48 ins. diam., bears N. 53° W., 12 lks. dist., with healed blaze.

and a new bearing tree