

# County Surveyor's Record, Douglas County, Oregon

16567

Dependent Resurvey of a Portion of the North Boundary,  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

## CHAINS

A fir, 12 ins. diam., bears S. 78 1/2° E., 56 lks.  
dist., mkd. T30S R6W S5 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, yew, maple, oak, hemlock, cedar, and madrone;  
undergrowth, poison oak, blackberry, salmonberry, hazel,  
arrowwood, wild strawberry, wild rose, fern, and young  
timber.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

(Restoring the survey by Addison R. Flint,  
U. S. Deputy Surveyor, in 1855,  
the resurvey by John M. Jelley and C. Albert White,  
Cadastral Surveyors, in 1964,  
and the resurvey by Lynn M. Roseberry,  
Cadastral Surveyor, in 1967)

From the 1/4 sec. cor. of secs. 4 and 5, monumented with an  
iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins.  
above ground, with brass cap mkd.

T 30 S R 6 W  
1/4  
S 5 | S 4  
1967

from which the remains of the original bearing trees

A root hole, bears S. 7° E., 45 lks. dist., with  
a down and decayed oak alongside, 30 ins. diam.,  
no marks visible on opened blaze.

and the remains of bearing trees mkd. by John H. Markham,  
Jr. Registered Engineer No. 2880, in 1957

A white oak, 9 ins. diam., bears S. 72 1/2° E., 95  
lks. dist., with fragmentary scribe marks visible  
on partially healed blaze. (Record, S 74° E.)

A white oak, 9 ins. diam., bears S. 5 3/4° W., 85 1/2 lks.  
dist., with fragmentary scribe marks visible on  
partially healed blaze.

A fir snag, 12 ins. diam., bears S. 84 3/4° W., 33 1/2  
lks. dist., with scribe marks 1/4 S5 BT visible  
on bark.

and a bearing tree mkd. by James W. Byron, Deputy County  
Surveyor, in 1962

A cedar, 19 ins. diam., bears N. 47 1/2° E., 104 lks.  
dist., with fragmentary scribe marks visible on  
partially healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears S. 73 3/4° W., 44 lks.  
dist., mkd. 1/4 S5 BT.

N. 8° 59' W., bet. secs. 4 and 5, marking and blazing the  
true line.