

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

16568

CHAINS	
7.35	Ascend 5 ft. over broken SW. slope. Ridge, bears N. 20° W., and S. 85° E.; desc. 320 ft. over NE. slope.
18.09	Point for the N 1/16 sec. cor. of secs. 4 and 5. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground with brass cap mkd. <div style="text-align: center; margin: 10px 0;">N 1/16 S 5   S 4 1980</div> from which <div style="margin-left: 40px; margin-top: 10px;">A fir, 12 ins. diam., bears S. 51° E., 6 1/2 lks. dist., mkd. N 1/16 S4 BT.  A fir, 13 ins. diam., bears N. 67° W., 12 1/2 lks. dist., mkd. N 1/16 S5 BT.</div> Descend 25 ft. over NE. slope.
27.25	Bottom of descent, drains N. 50° E.; asc. 20 ft. over SE. slope.
29.45	Spur, slopes N. 55° E.; desc. 45 ft. over NE. slope.
33.05	Ravine, drains N. 80° E.; asc. 25 ft. over SE. slope.
35.10	The cor. of secs. 4 and 5 only, on the N. bdy. of the Tp.  Land, mountainous. Soil, rocky clay. Timber, fir, yew, hemlock, oak, madrone, and cedar; undergrowth, poison oak, blackberry, salmonberry, arrowwood, hazel, fern, and young timber.
From the 1/4 sec. cor. of secs. 5 and 8, perpetuated and recorded by L.G. Hicks, Civil Engineer, in 1910, further perpetuated and recorded by John H. Markham, Jr., Deputy County Surveyor, in 1951, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 12 ins. above ground from which the remains of the original bearing tree: <div style="margin-left: 40px; margin-top: 10px;">A sawed fir stump, 25 ins. diam., bears N. 80° E., 13 lks. dist., (to face), with axe marks in bark.</div> and the remains of bearing trees mkd. by Markham, <div style="margin-left: 40px; margin-top: 10px;">A sawed fir stump, 33 ins. diam., bears N. 51° E., 24 lks. dist., with scribe marks 1/4 S5 visible on bark.  A sawed madrone stump, 20 ins. diam., bears S. 58° E., 88 lks. dist., with scribe marks 1/4 S8 CS BT visible on open blaze.</div> At the corner point  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly over iron pipe, with brass cap mkd.	