

County Surveyor's Record, Douglas County, Oregon

16569

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

T 30 S R 6 W

1/4 $\frac{S 5}{S 8}$

1980

from which new bearing trees

A fir, 9 ins. diam., bears N. 58 3/4° E., 7 lks.
dist., mkd. 1/4 S5 BT.

A fir, 8 ins. diam., bears S. 73 1/2° W., 115 lks.
dist., mkd. 1/4 S8 BT.

N. 89° 19' W., bet. secs. 5 and 8.

Descend 150 ft. over NW. slope, through heavy timber and dense undergrowth.

1.50 Gravelled road, 20 lks. wide, bears N. 80° E. and S. 80° W.

6.75 Ravine, drains N.; asc. 120 ft. over NE. slope.

12.45 Spur, slopes N. 10° W.; desc. 25 ft. over N. slope, also gravelled road, 20 lks. wide, bears S. 50° E. and W.; continue along S. edge of road.

19.50 Spur, slopes N. 50° W.; desc. 5 ft. over SW. slope, also junction of gravelled roads, bears E., S. 25° W., in curve, and S. 85° W.

20.40 Point for the W 1/16 sec. cor. of secs. 5 and 8.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 5}{S 8}$

1980

from which

A fir, 6 ins. diam., bears S. 18° E., 60 lks.
dist., mkd. W 1/16 S8 BT.

A fir, 5 ins. diam., bears N. 13 1/2° W., 35 lks.
dist., mkd. W 1/16 S5 BT.

Corner is located on N. edge of gravelled road, 20 lks. wide, bears E. and W.

Descend 460 ft. over SW. slope.

23.60 Gravelled road, 15 lks. wide, bears N. 60° W. and S 85° E.

37.90 Thompson Creek, 5 lks. wide, course N. 10° W.; asc. 45 ft. over NE. slope.

40.80 The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

T 30 S R 6 W

$\frac{S 6 | S 5}{S 7 | S 8}$

1963