

# County Surveyor's Record, Douglas County, Oregon

16570

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 30 S., R. 6 W., Willamette Meridian, Oregon

**CHAINS**

from which the remains of the original bearing trees

A fir snag, 12 ins. diam., bears S. 45° W., 75 lks. dist., with scribe marks 30 visible on opened blaze.

and the remains of bearing trees mkd. by Jelley and White

A fir stump, 15 ins. diam., bears N. 85° E., 78 lks. dist., with scribe marks 30S R6W S5 visible on opened blaze.

A cedar, 10 ins. diam., bears S. 14° E., 35 lks. dist., with scribe marks R6W S8 BT visible on open blaze.

A cedar, 10 ins. diam., bears S. 51 1/2° W., 23 lks. dist., with scribe marks 30S R6W S7 visible on open blaze.

A fir, 12 ins. diam., bears N. 87° W., 112 lks. dist., with illegible scribe marks visible on partially healed blaze.

and a new bearing tree

A cedar, 5 ins. diam., bears N. 25° E., 34 1/2 lks. dist., mkd. X BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, madrone, oak, hemlock, and maple; undergrowth, poison oak, fern, hazel, arrowwood, blackberry, thimbleberry, and young timber.

N. 1° 34' E., bet. secs. 5 and 6.

Descend 70 ft. over NE. slope, through heavy timber and dense undergrowth.

6.70 Thompson Creek, 5 lks. wide, course N. 45° W.; asc. 135 ft. over SW. slope.

14.90 Spur, slopes N. 65° W.; desc. 145 ft. over NW. slope.

19.52 The S 1/16 sec. cor. of secs. 5 and 6, established by L. G. Hicks, Civil Engineer, in 1910, and is accepted as the corner, determined at record bearing and distance from bearing trees mkd. by Hicks:

A cedar, 30 ins. diam., bears N. 43 1/2° E., 33 lks. dist., no marks visible.

A fir, 30 ins. diam., bears S. 60° E., 24 lks. dist., with scribe marks 1/16 visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16  
S 6 | S 5  
1980