

County Surveyor's Record, Douglas County, Oregon

16571

Dependent Resurvey, Portion of Subdivisional Lines,
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS

from which new bearing trees

A fir, 6 ins. diam., bears N. 49 1/2° E., 17 lks.
dist., mkd. S 1/16 S5 BT.

A fir, 11 ins. diam., bears N. 86° W., 33 lks.
dist., mkd. S 1/16 S6 BT.

N. 1° 34' E., beginning new measurement.

Descend 45 ft. over NW. slope.

- 1.40 Creek, 4 lks. wide, course S. 75° W.; asc. 355 ft. over SE. slope.
- 3.95 Dirt road, 15 lks. wide, bears N. 75° E. and S. 70° W.
- 16.95 Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.
- 18.40 Spur, slopes S. 65° W.; desc. 5 ft. over NW. slope.
- 19.52 The 1/4 sec. cor. of secs. 5 and 6, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1962, monumented with an iron post, 1 1/4 ins. diam., firmly set, projecting 16 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE
T 30 S R 6 W
1/4 S 6 | S 5
1962

from which the remains of the original bearing trees

A root hole, bears N. 35° E., 380 lks. dist., with a down oak alongside, size indeterminate, no marks visible.

A white oak, 37 ins. diam., bears N. 47° W., 90 lks. dist., with illegible scribe marks visible on opened blaze.

and bearing trees mkd. by Byron

A cedar, 18 ins. diam., bears N. 4° E., 48 1/2 lks. dist., with healed double blaze.

A white oak, 13 ins. diam., bears N. 61° W., 50 1/2 lks. dist., with healed double blaze.

N. 4° 58' W., beginning new measurement

Descend 20 ft. over NW. slope.

- 1.55 Creek, 3 lks. wide, course S 50° W.; asc. 335 ft. over broken SW. slope.
- 18.51 The N 1/16 sec. cor. of secs. 5 and 6, established by Howard W. Johnstone, Registered Land Surveyor, No. 498, in 1977, and is accepted as the corner, monumented with an iron rod, 5/8 ins. diam., firmly set, projecting 6 ins. above ground, with aluminum cap mkd.

N 1/16 S 6 | S 5

from which bearing trees mkd. by Johnstone