

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 16572
T. 30 S., R. 6 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 20 ins. diam., bears N. 70° E., 27 1/2 lks. dist., with scribe marks 1/16 BT visible on opened blaze.</p> <p>A double pine, 18 ins. diam., bears S. 11° W., 78 1/2 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 5° 02' W., beginning new measurement.</p> <p>Ascend 60 ft. over SW. slope.</p>
0.05	Barbed wire fence, extends E. and W.
3.15	Spur, slopes S. 65° W.; desc. 335 ft. over broken NW. slope.
16.70	Creek, 5 lks. wide, course W.; asc. 35 ft. over SW. slope.
18.05	<p>The cor. of secs. 5 and 6 only, on the N. bdy. of the Tp.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, cedar, fir, hemlock, maple, madrone, pine, oak, and ash; undergrowth, fern, poison oak, blackberry, thimbleberry, Oregon grape, arrowwood, hazel, vine maple, and young timber.</p>
<p>Subdivision of Section 5, T. 30 S., R. 6 W., Willamette Meridian, Oregon</p>	
<p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 2° 54' W., on the N. and S. center line of sec. 5.</p> <p>Descend 205 ft. over NW. slope, through heavy timber and dense undergrowth.</p>	
0.35	Gravelled road, 20 lks. wide, bears N. 50° E. and S 50° W.
16.10	Spur, slopes N. 55° W.; desc. 75 ft. over NE. slope.
18.05	Gravelled road, 20 lks. wide, bears N. 55° W. and S 55° E.
19.70	<p>Point for the center S 1/16 sec. cor. of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} C \\ S\ 1/16 \left S\ 5 \\ C \\ 1980 \end{array}$ </div> <p>from which</p> <p>A fir, 5 ins. diam., bears S. 45 1/2° E., 42 lks. dist., mkd. X BT.</p> <p>A fir, 6 ins. diam., bears N. 69 1/2° W., 17 lks. dist., mkd. CS 1/16 S5 BT.</p>