

County Surveyor's Record, Douglas County, Oregon

16573

Subdivision of Section 5, T. 30 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS

- Descend 140 ft. over NE. slope.
- 23.70 Creek, 5 lks wide, course N. 70° W.; asc. 175 ft. over SW. slope.
- 32.55 Gravelled road, 20 lks. wide, bears N. 55° W. and S. 55° E.
- 33.90 Spur, slopes S. 50° W.; desc. 80 ft. over NW. slope.
- 35.65 Gravelled road, 20 lks. wide, bears N. 60° E. and S 25° W.
- 39.40 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap. mkd.

T 30 S R 6 W
C 1/4 S 5
1980

from which

- A fir, 5 ins. diam., bears N. 28° E., 14 lks. dist., mkd. C 1/4 S5 BT.
- A fir, 5 ins. diam., bears N. 45 1/2° W., 12 lks. dist., mkd. C 1/4 S5 BT.
- Set a 6 ft. fiberglass fence post alongside iron post.

Descend 20 ft. over NW. slope.

- 40.50 Creek, 5 lks. wide, course S. 55° W.; asc. 30 ft. over SW. slope.
- 41.20 Spur, slopes W.; desc. 5 ft. over NW. slope.
- 41.55 Creek, 1 lk. wide, course W.; desc. 5 ft. over NW. slope.
- 45.20 Creek, 1 lk. wide, course S. 45° W.; asc. 255 ft. over SW. slope.
- 48.95 Woven wire fence, bears S. 55° W. and N. 55° E.
- 57.40 Point for the center N 1/16 sec. cor. of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 diam., 24 ins. in the ground, with brass cap mkd.

C
N 1/16 | S 5
C
1980

from which

- A cedar, 16 ins. diam., bears S. 36 1/2° E., 149 lks. dist., mkd. CN 1/16 S5 BT.
- A cedar, 18 ins. diam., bears N. 51° W., 59 lks. dist., mkd. CN 1/16 S5 BT.
- Set a 6 ft. fiberglass fence post alongside iron post.