

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 5, T. 30 S., R. 6 W.,
Willamette Meridian, Oregon

16574

CHAINS

Corner is located 3 lks. west of fence corner, with fences extending E., W., and S. 5° E.

Ascend 150 ft. over SW. slope.

64.35 Dirt road, 15 lks. wide, bears N. 55° E. and S. 65° W.

65.40 Dirt road, 15 lks. wide, bears N. 50° W. and S. 85° E.

69.15 Spur, slopes N. 85° W.; desc. 45 ft. over NW. slope.

73.15 Creek, 2 lks. wide, course S. 55° W.; asc. 35 ft. over SE. slope.

74.64 The 1/4 sec. cor. of sec. 5 only, on the N. bdy. of the Tp.

From the 1/4 sec. cor. of secs. 4 and 5.

N. 89° 48' W., on the E. and W. center line of sec. 5.

Descend 75 ft. over NW. slope.

1.30 Gravelled road, 25 lks. wide, bears N. 5° E. and S. 10° E., in curve.

4.00 Ravine, drains S. 25° W.; asc. 5 ft. over SE. slope.

6.65 South edge of gravelled road, 25 lks. wide, bears N. 80° E. and N. 30° W., in curve.

6.70 Spur, slopes S. 5° W.; desc. 115 ft. over NW. slope.

13.10 Bottom of descent, drains S. 45° W.; asc. 35 ft. over SE. slope.

18.00 Spur, slopes S. 50° W.; desc. 55 ft. over NW. slope.

21.19 Point for the center E 1/16 sec. cor. of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{S } 5 \quad \text{C} \\ 1980 \end{array}$$

from which

A fir, 6 ins. diam., bears S. 73° W., 70 lks. dist., mkd. CE 1/16 S5 BT.

A fir, 5 ins. diam., bears N. 16° W., 25 lks. dist., mkd. X BT.

Descend 430 ft. over NW. slope.

28.40 Gravelled road, 25 lks. wide, bears N. 5° E. and S. 5° W.

31.55 Gravelled road, 25 lks. wide, bears N. and S.

39.65 Gravelled road, 25 lks. wide, bears N. 35° E. and S. 35° W.

42.38 The center 1/4 sec. cor. of sec. 5.