

County Surveyor's Record, Douglas County, Oregon


16575

Subdivision of Section 5, T. 30 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS

- Descend 40 ft. over NW. slope.
- 44.75 Creek, 2 lks. wide, course S. 60° W.; desc. 20 ft. over NW. slope.
- 45.65 Creek, 3 lks. wide, course S.; asc. 50 ft. over SE. slope.
- 53.35 Spur, slopes S.; desc. 10 ft. over SW. slope.
- 54.80 Creek, 2 lks. wide, course S.; asc. 15 ft. over SE. slope.
- 61.26 Point for the center W 1/16 sec. cor. of sec. 5.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A cedar, 7 ins. diam., bears N. 2 1/2° W., 101 lks. dist., mkd. CW 1/16 S5 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 12 1/2° E., 85 lks. dist., with brass cap mkd. CS 1/16 S5 RM 1980 and an arrow pointing to the corner.

and a bearing tree of which I have no record

A cedar, 26 ins. diam., bears S. 71° W., 92 lks. dist., with scribe marks CW 1/16 S5 BT visible on open blaze.

Ascend 5 ft. over SE. slope.

- 62.25 Creek, 1 lk. wide, course S.; asc. 70 ft. over SE. slope.
- 67.70 Spur, slopes S.; desc. 20 ft. over SW. slope.
- 69.40 Creek, 1 lk. wide, course S.; asc. 105 ft. over SE. slope.
- 73.95 Spur, slopes S. 10° E.; asc. 5 ft. over SE. slope.
- 78.00 Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W.
- 78.85 Spur, slopes S. 30° W.; desc. 25 ft. over NW. slope.
- 80.14 The 1/4 sec. cor. of sec. 5 and 6.

From the center E 1/16 sec. cor. of sec. 5.

N. 5° 57' W., on the N. and S. center line of the NE 1/4 of sec. 5.

Descend 90 ft. over NW. slope, through heavy timber and dense undergrowth.

- 5.65 Ravine, drains S. 70° W.; asc. 50 ft. over SW. slope.
- 9.70 Spur, slopes S. 70° W.; desc. 110 ft. over NW. slope.