

County Surveyor's Record, Douglas County, Oregon

16577

Subdivision of Section 5, T. 30 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS	
	Descend 100 ft. over NW. slope.
5.00	Creek, 1 lk. wide, course S. 35° W.; asc. 135 ft. over SE. slope.
12.70	Spur, slopes S. 25° W.; desc. 70 ft. over SW. slope.
15.35	Ravine, drains S. 40° E.; asc. 15 ft. over SE. slope.
20.23	The center N 1/16 sec. cor. of sec. 5.
<p>From the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>N. 0° 41' W., on the N. and S. center line of the SW 1/4 of sec. 5.</p> <p>Ascend 5 ft. over SW. slope, through heavy timber and dense undergrowth.</p>	
0.80	Spur, slopes N. 55° W.; desc. 60 ft. over NE. slope.
5.75	Spur, slopes N. 5° E.; desc. 345 ft. over NW. slope.
11.50	Gravelled road, 20 lks. wide, bears N. 85° E. and W.
18.85	Ravine, drains N. 10° E.; asc. 10 ft. over SE. slope.
19.59	Point for the SW 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the SW 1/4 of sec. 5.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	SW 1/16 S 5 1980
	from which
	A fir, 7 ins. diam., bears S. 22° E., 16 1/2 lks. dist., mkd. SW 1/16 S5 BT.
	A fir, 14 ins. diam., bears S. 54° W., 29 lks. dist., mkd. SW 1/16 S5 BT.
	Ascend 10 ft. over SE. slope.
22.45	Spur, slopes E.; desc. 105 ft. over NE. slope.
24.95	Creek, 10 lks. wide, course S. 85° W.; asc. 165 ft. over SW. slope.
38.40	Woven wire fence, bears N. 70° E. and S. 70° W.
39.18	The center W 1/16 sec. cor. of sec. 5
<p>From the center S 1/16 sec. cor. of sec. 5.</p> <p>N. 89° 32' W., on the E. and W. center line of the SW 1/4 of sec. 5.</p> <p>Ascend 5 ft. over NE. slope, through heavy timber and dense undergrowth.</p>	