

County Surveyor's Record, Douglas County, Oregon

Subdivision of Section 5, T. 30 S., R. 6 W.,
Willamette Meridian, Oregon

16578

CHAINS

- 2.60 Gravelled road, 15 lks. wide, bears N. 55° W. and S. 65° E.
- 3.70 Spur, slopes N. 35° W.; desc. 195 ft. over NW. slope.
- 9.50 Creek, 2 lks. wide, course N. 40° W.; asc. 60 ft. over NE. slope.
- 13.60 Spur, slopes N. 30° E.; desc. 45 ft. over NW. slope.
- 15.55 Ravine, drains N.; asc. 45 ft. over NE. slope.
- 17.55 Spur, slopes N. 10° W.; desc. 55 ft. over NW. slope.
- 19.45 Creek, 1 lk. wide, course N. 5° E.; asc. 10 ft. over NE. slope.
- 19.64 The SW 1/16 sec. cor. of sec. 5.
Ascend 40 ft. over NE. slope.
- 26.35 Spur, slopes N.; desc. 60 ft. over NW. slope.
- 29.55 Head of ravine, drains N.; asc. 15 ft. over NE. slope.
- 31.25 Spur, slopes N. 10° E.; desc. 45 ft. over NW. slope.
- 33.20 Ravine, drains N. 10° E.; asc. 20 ft. over NE. slope.
- 34.40 Spur, slopes N. 10° E.; desc. 65 ft. over NW. slope.
- 39.28 The S 1/16 sec. cor. of secs. 5 and 6.
-
- From the center W 1/16 sec. cor. of sec. 5.
- N. 3° 59' W., on the N. and S. center line of the NW 1/4 of sec. 5.
- Ascend 445 ft. over broken S. slope, through heavy timber and dense undergrowth.
- 18.26 Point for the NW 1/16 sec. cor. of sec. 5, at intersection with the E. and W. center line of the NW 1/4 of sec. 5.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- NW 1/16 S 5
1980
- from which
- A fir, 26 ins. diam., bears S. 48 1/4° E., 225 lks. dist., mkd. NW 1/16 S5 BT.
- A cedar, 10 ins. diam., bears N. 55 3/4° W., 82 lks. dist., mkd. NW 1/16 S5 BT.
- Corner is located in woven wire fence, bears E. and W.
- Ascend 130 ft. over broken S. slope.
- 18.35 Dirt road, 15 lks. wide, bears N. 50° E. and S. 45° W.
- 28.50 Spur, slopes W.; desc. 295 ft. over NE. slope.